

BioCompact 210/210



Biostorage you can depend on



BioCompact RR210/210

The **BioCompact 210/210** is a general purpose combination refrigerator and/or freezer cabinet with a small footprint, designed for a wide range of basic biostorage purposes where the prime focus is on dependability and exceptional performance.

The **BioCompact 210/210** provides you with significantly better performance than any other cabinets in this segment, on account of a refrigeration system that does away with cold walls that can damage the contents and a unique air distribution system for storing ordinary biomaterial under consistent, stable conditions.

The design of the **BioCompact 210/210** ensures you lots of ways to deal with individual storage needs, thanks to many different optional combinations of refrigeration ranges, the versatile interior layout and a comprehensive selection of fixtures and fittings. The small footprint of this design also makes it the perfect biostorage unit for use in confined spaces.

The **BioCompact 210/210** uses environmentally responsible HFC-free foam propellants and is available with CFC-free or HFC-free refrigerants. Based on decades of specialist know-how, these biostorage units are exceptionally energy-efficient, and are the best performers on the market in relation to Scandinavian standards.

Available in either white or stainless steel finish, with a one-piece moulded ABS inner lining. Shelves and drawers are mounted in U-shaped rails moulded into the plastic walls.



II 3G Ex nA nC nL IIB T6
II 3G Ex nA nC nL IIB T4
TÜV 10 ATEX 381563



The BioCompact 210/210 models are available as refrigerator or freezer in either white or stainless steel finish. BioCompact refrigerators can be equipped with a solid door with lock or glass door with LED light and lock. BioCompact freezers are equipped with a solid door with lock.

Biostorage
you can
depend on



BioCompact 210/210



Biostorage you can depend on

Top panel with BioLine control unit

The MPC unit is specially developed for users of BioLine storage cabinets. Among its many features are acoustic door alarm, and a voltage free contact (NO/NC) for remote alarms. The display can be locked.



Access port

24.5 mm port for ease of access, e.g. sensors for external temperature surveillance.




Voltage free contact

Provides a remote alarm in case of power failure or door alarm, with separate delay.




Finned tube evaporator

Using a refrigeration system based on a finned tube evaporator is unique for biostorage products in this segment, and provides unparalleled benefits. The design results in a refrigerated storage space with no cold walls that can damage any delicate items stored in the cabinet. This also makes it possible to ensure even better temperature stability inside the cabinet.




Refrigeration systems

Every Combi cabinet is equipped with two independent refrigeration systems and control units, for maximum safety and performance.



Shelves and drawers

A wide range of versatile interior fittings and layouts is available. The operating specifications and the interior layout can both be customised.



ATEX

All BioCompact models comply with ATEX Cat.3 Zone 2 requirements, both internal and externally, allowing for placement in locations where explosive gas atmospheres may be present.

Technical specifications	RR210/RF210	RR210/RR210	RF210/RF210
Temperature range	+15/+2 °C and -5/-25°C	+15/+2 °C and +15/+2°C	-5/-25°C and -5/-25°C
Ambient temperature range	Solid door 10/35 °C; glass door (RR) 10/32 °C		
Control Unit	Gram Control Unit with voltage-free contact, acoustic and visual door alarms that can be programmed individually, and calibration function		
Material interior	ABS lining		
Material exterior	Lacquered steel or stainless steel		
Dimensions mm (W x D x H)	595 x 640 x 1700		
Gross volume	125 litres/4.4 cubic feet and 125 litres/4.4 cubic feet		
Net volume	104 litres/3.7 cubic feet and 104 litres/3.7 cubic feet		
Modules for shelves and drawers	Shelves 2 x 7, drawers 2 x 4, baskets 2 x 2		
Insulation	50 mm polyurethane with CFC and HFC-free cyclopentane propellant		
Refrigerant	R600 / R134A		
Refrigeration capacity at -10 °C	R600a 154 Watt / R134a 150 Watt	R600a 154 Watt / R134a 150 Watt	-
Refrigeration capacity at -25 °C	R600a 156 Watt / R134a 149 Watt	-	R600a 156 Watt / R134a 149 Watt
Energy consumption	1.7 kWh/24h	1.2 kWh/24h	2.2 kWh/24h
Noise level	40,9 dB(A)	39,1 dB(A)	42,1 dB(A)
Base	Legs*		
Connection	230 V, 50 Hz		
Air system	BioLine ventilated air distribution system		
Defrost system	Automatic smart defrost with re-evaporation of defrost water		

AIR DISTRIBUTION

The unique Gram BioLine air distribution system makes sure the temperature inside the cabinet remains stable at all times. With the finned tube evaporator placed in the top, there are no cold walls inside the cabinet.

* The cabinets can be delivered with castors or legs or prepared for mounting on a plinth at no extra charge.



Gram Commercial A/S // Aage Grams Vej 1 // DK-6500 Vojens
Tel. +45 7320 1300 // info@gram-bioline.com // gram-bioline.com